

TECHNICAL INFORMATION PRELIMINARY



- Common Paper PSA Label -

Fluorescent Yellow/RV20N/GG62

PHYSICAL CHARACTERISTICS

Facestock

A one side coated fluorescent yellow paper. Offers top print quality by letterpress, offset, flexo.

Basis weight	ISO 536	: 75 gsm
Caliper	ISO 534	: 76 µm
Surface treatment		: Colour top coated

Adhesive

A general purpose emulsion acrylic removable adhesive with good initial tack and superior removability. It is compliant US FDA 21 CFR 175.105 (Adhesive) for food packaging & food processing as well as ECC 88/378/EEC, CEN EN71, PART 3.

Minimum Application Temperature	: -12°C
Product Functional Service Temperature:	-30°C / +80°C

Liner

A super-calendered blue glassine paper.

Basis weight	ISO 536	: 62 gsm
Caliper	ISO 534	: 55 µm

PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	5.0 N/25mm
Adhesion to Stainless Steel	FINAT FTM1	3.5 N/25mm (20mins)
Total Product Caliper	ISO 534	144 µm

Shelf life

1 year when stored at 22°C and 50% RH