

**Product:** Moroccan Canvas Satin



**Category:** Display & Visual - Aqueous

**Country of Origin:** Germany

### Technical specifications:

Parameters	Value	
Weight DIN EN ISO 536	g/m	340 ± 25
Thickness DIN EN ISO 534	um	400 ± 25
	mil	15.7 ± 1.0
Colour Elrepho UVO (D65) ISO 2469	L	94.3 ±1.0
	a	-0.8 ±0.5
		2.4 ±1.0
	delta b	2.9 ±1.0
CIE Whiteness (D65/10°) Min ISO 2469		>130
Opacity min. ISO 2469	%	>98

### Useful Tips

Instant Dry. High light fastness with pigmented inks. Free of harmful substances (certified by Oeko-Tex<sup>®</sup>, Standard 100, 12.0.09048). Store material only in original packaging under normal climatic conditions (23 deg, 50% RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24hours before usage.

### Conversion<sup>+</sup>

- |  |   |
|--|---|
| <input type="checkbox"/> Flat bed cutters        | <input type="checkbox"/> Cold overlaminating                |
| <input type="checkbox"/> Friction bed cutters    | <input checked="" type="checkbox"/> Aqueous (dye & pigment) |
| <input type="checkbox"/> Die cutters             | <input type="checkbox"/> Latex                              |
| <input type="checkbox"/> Thermal transfer screen | <input type="checkbox"/> Solvent                            |
| <input type="checkbox"/> Screen printing         | <input type="checkbox"/> Eco Solvent                        |
| <input type="checkbox"/> Printing offset         | <input type="checkbox"/> UV Ink jet                         |

<sup>+</sup>Always test with your combination of printer and inks prior to commercial use

### Roll Sizes

610mm x 15m	126614
1118mm x 15m	126613

### Common Applications

Canvas on stretcher frames  
Photos  
Art reproduction