

Technical specification sheet

Ball & Doggett

ballanddoggett.com.au



Product: Onyx Recycled

Category: Display & Visual - Rigid

Country of Origin: Australia

Technical Specifications:

Property	
Thickness	3.3mm 5.3mm
Material	100% Post Industrial Polypropylene
Corona Treatment	Both sides - guage tolerance ± 0.1 mm
Colour	Mottled White *
Recommended service temp.	0Deg to 50Deg

* Sheet colour will vary from batch to batch dependnet on recycle feedstock



Conversion⁺

- | | |
|-----------------------------------------------------|-------------------------------------------------------|
| <input type="checkbox"/> Flat bed cutters | <input type="checkbox"/> Cold overlaminating |
| <input type="checkbox"/> Friction fed | <input type="checkbox"/> Aqueous |
| <input type="checkbox"/> cutters Die cutting | <input type="checkbox"/> Latex inkjet |
| <input type="checkbox"/> Thermal transfer | <input type="checkbox"/> Eco Solvnt inkjet |
| <input checked="" type="checkbox"/> Screen printing | <input type="checkbox"/> Solvent inkjet |
| <input type="checkbox"/> Offset printing | <input checked="" type="checkbox"/> UV curable Inkjet |

⁺Always test with your combination of printer and inks prior to commercial use.

Sheet Sizes

1220 x 2440mm	130708
1800 x 1220mm	131036

Common Applications

Packaging products	POS Display
Fabrication	Signage
Screen & Digital printing	