

**Product:** Rhino Aqueous Blockout Film BA100



**Category:** Display & Visual - Aqueous

**Country of Origin:** Korea

## Technical specifications:

Parameters	Unit	Range
Thickness	ums	240
Basis weight	g/m2	215
Base material	Polyethylene (PET) / Polypropylene (PP)	
Opacity	%	100
Coating	Porous	-
Lamination	optional	-
Printing Temperature	Degree	15~30°C
	Humidity	30~60 %

## Conversion<sup>+</sup>

- |  |   |
|--|---|
| <input type="checkbox"/> Flat bed cutters        | <input type="checkbox"/> Cold overlaminating                |
| <input type="checkbox"/> Friction bed cutters    | <input checked="" type="checkbox"/> Aqueous (dye & pigment) |
| <input type="checkbox"/> Die cutters             | <input type="checkbox"/> Latex                              |
| <input type="checkbox"/> Thermal transfer screen | <input type="checkbox"/> Solvent                            |
| <input type="checkbox"/> Screen printing         | <input type="checkbox"/> Eco Solvent                        |
| <input type="checkbox"/> Printing offset         | <input checked="" type="checkbox"/> UV Ink jet              |

<sup>+</sup>Always test with your combination of printer and inks prior to commercial use

## Roll Sizes

914mm x 30m	148957
1067mm x 30m	148958
1270mm x 30m	148959

## Common Applications

Roll up stands  
Indoor POS/POP Signage  
Instruction plates shop & Exhibition works  
Tradeshaw panels  
Posters