

Product: Rhino - PP White Film Aqueous Inkjet PH900



Category: Display & Visual - Aqueous

Technical specifications:

Parameters	Value
Basis weight	130 g/m ²
Thickness	205 ums
Base material	Polypropylene
Surface	Matt
Coating	Porous
Inner core (inch)	2"

General information

- Double coated polypropylene film with curl-free and deep blacks.
- Durable base film has a water resistant coating and a Ultra white surface.
- Reducing light or reflections on the printed surface.
- Printing Temp : Temperature 15 ~ 30deg (59 ~ 86 Farenheit) / Humidity 30 ~ 60%
- Lamination : Lamination is optional.
- Storage : Temperature 10 ~ 30deg (50 ~ 77 Farenheit) / Relative Humidity 50%
- Shelf Life : One year stored in original packaging at recommended conditions.(Coating warranty guaranteed for 6 months from date of purchase)

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.

Conversion⁺

- | | |
|--|---|
| <input type="checkbox"/> Flat bed cutters | <input type="checkbox"/> Cold overlaminating |
| <input type="checkbox"/> Friction bed cutters | <input checked="" type="checkbox"/> Aqueous (dye & pigment) |
| <input type="checkbox"/> Die cutters | <input type="checkbox"/> Latex |
| <input type="checkbox"/> Thermal transfer screen | <input type="checkbox"/> Solvent |
| <input type="checkbox"/> Screen printing | <input type="checkbox"/> Eco Solvent |
| <input type="checkbox"/> Printing offset | <input checked="" type="checkbox"/> UV Ink jet |

⁺Always test with your combination of printer and inks prior to commercial use

Roll Sizes

914mm x 30m	126258
1067mm x 30m	127544

Common Applications

Photo realistic prints	Shop Displays and Exhibits
Posters	Indoor POS/POP