

Product: Adestor Vellum Removable

Adestor

Category: Folio Papers - Self Adhesive

Country of origin: Spain

Technical specifications:

FACESTOCK

Offset

Description Supercalendered uncoated woodfree paper.

Applications Ideal for all types of applications: variable label information (barcodes, expiry date, price, weight etc.)

Printing techniques Suitable for printing on flexo (all types), conventional offset, offset UV, letterpress (conventional and UV), screen printing, thermal transfer, laser, hot stamping.

Property	Norm	Units	Value	Tolerance
Substance	75	g/m ²	75	70-76
Thickness	ISO 534	µm	70	± 2
Bekk smoothness	ISO 5627	s	≥ 250	
Brightness ISO	ISO 2470-2	%	101.5	± 2
Whiteness CIE	ISO 11475	%	158.2	± 5
Opacity	ISO 2471	%	89	-2
Tensile strength MD/CD	ISO 1924-2	kN/m	5.0/3.0	-1

Certificates

Product approvals and usage certificates

[Contact with foodstuff \(BfR XXXVI\) - Facestock and Liners \(paper\)](#)

[Toy safety European directive 2009/48/CE](#)

[Packaging and packaging waste Directive 94/62/CE](#)

[Electric and electronic equipment \(RoHS\) Directive 2002/95/CE](#)

- * Values are subject to change without notice. Last updated 4/4/2012.
- * The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Product: Adestor RA678

Adestor

Category: Folio Papers - Adhesive Sheets

Technical specifications:

ADHESIVE

RA678

Description Acrylic removable adhesive with clean removability from most surfaces. Trial is recommended when using this adhesive in new or unknown surfaces

Shelf life From the date of manufacture 1 year in 20°C and RH 50%

Property	Norm	Units	Value	Tolerance
Adhesion (Peel stainless steel 1 week)	FTM 1	N/25mm	1,7	1 - 2,9
Shear (1kg, in ² /glass)	FTM 8	min	120	≥ 60
Tack (Quick Stick stainless steel)	FTM 9	N	1,2	0,7 - 1,7
Minimum labelling temperature		°C	5	
Minimum service temperature		°C	-20	
Maximum service temperature.		°C	+80	

Certificates

Product approvals and usage certificates

EN 71-3 Toy safety

Packaging and packaging waste Directive 94/62/CE

- Values are subject to change without notice. Last updated 7/28/2014.
- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.

Product: Adestor WK80

Adestor

Category: Folio Papers - Adhesive Sheets

Technical specifications:

LINER

WK80

Description One-side coated white liner with good lay-flat characteristics. Suitable for sheeting. Available only in solid back

Color White

Property	Norm	Units	Value	Tolerance
Substance	ISO 536	g/m ²	80	±4%
Thickness	ISO 534	µm	81	±4
Tensile strength MD/CD	ISO 1924-2	kN/m	4,6 / 2,3	-0,6 / -0,3

Certificates

Product approvals and usage certificates

Contact with foodstuff (BfR XXXVI) - Facestock and Liners (paper)

Packaging and packaging waste Directive 94/62/CE

EN 71-3 Toy safety

Electric and electronic equipment (RoHS) Directive 2002/95/CE

- Values are subject to change without notice. Last updated 7/27/2015.
- The technical information that appears in this document reflects our knowledge and experience, but should only be considered as a general guideline.