

Product: Raflatac Vellum (Removable)

Category: Folio Papers - Self Adhesive

Country of origin: Poland

Technical specifications:

SELF-ADHESIVE	SHEETS
FACE	VELLUM-FSC
Uncoated	CKG (sales code)
Product	Surface sized woodfree SC paper.
Use	Universal label paper for commercial and general labelling.

Typical technical values

Substance	70	g/m ²	ISO 536	
Caliper	70	µm	ISO 534	
Tensile strength MD	5.5	kN/m	ISO 1924/1	
Tensile strength CD	2.5	kN/m	ISO 1924/1	
Brightness	95	%	ISO 2470/1	
Roughness	2.7	µm	ISO 8791	PPS 10
Opacity	89	%	ISO 2471	
CIE Whiteness	133	%	ISO 11475	
Stiffness MD	0.18	mNm	ISO/DP 2493	
Stiffness CD	0.10	mNm	ISO/DP 2493	

Printability Offset, flexography, letterpress and dot-matrix.

Sustainability The product named as FSC is registered to SGSCH-COC-004879 FSC™ Mix credit.

Disclaimer Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to UPM Raflatac's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.

Product: Raflatac Vellum (Removable)

Category: Folio Papers - Self Adhesive

Country of origin: Poland

Technical specifications:

ADHESIVE	SR24
Removable	SR24 (sales code)
Type	Removable adhesive for sheets.
Composition	Acrylic, water borne.
Use	A general purpose removable adhesive designed for sheets laminates. Good long-term removability. Good cohesion and adhesion at difficult substrates.

Typical technical values

Tack min	2	N	FTM 9
Shear min	6	h	FTM 8
Labelling temperature min	5	°C	
Service temperature min	0	°C	
Service temperature max	80	°C	

Limitations Not recommended for labelling PVC or acrylic coated surfaces, long term removability might be restricted.

Approvals Please see DoC

Shelf life From the date of manufacture 2 years at +20 deg C and RH 50%. Prolonged storage at higher temperatures and/or humidity levels will shorten the shelf life.

Disclaimer The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to UPM Raflatac's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.

Product: Raflatac Vellum (Removable)

Category: Folio Papers - Self Adhesive

Country of Origin: Poland

Technical specifications:

SELF-ADHESIVE

BACKING

Kraft

Product

Use

SHEETS

KRAFT SPECIAL 90 FSC

EJB (sales code)

White woodfree kraft backing paper

Backing paper for reels and sheets in information labelling. Not to be used in photocell dispensing systems.

Typical technical values

Substance	86	g/m ²	ISO 536
Caliper	87	µm	ISO 534
Tensile strength MD	8.7	kN/m	ISO 1924
Tensile strength CD	3.8	kN/m	ISO 1924

Sustainability

The product named as FSC is registered to SGSCH-COC-004879 FSC TM Mix Credit.

Disclaimer

The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All our products are sold subject to UPM Raflatac's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.