

## TECHNICAL INFORMATION PRELIMINARY



- Rubber Hotmelt PSA Label -

## Gloss White BOPP60 TC/PR80T/WG62

### PHYSICAL CHARACTERISTICS

#### Facestock

A bright gloss white, top-coated BOPP film. Can be printed by letterpress, screen, flexo and gravure, using UV or solvent-based inks.

Caliper                    ISO 534                    : 60 µm

#### Adhesive

Hotmelt pressure sensitive adhesive, permanent type, with universal adhesion properties to various substrates and excellent die cutting properties. Meets composition requirements of indirect food additives regulation FDA 21-CFR-175.105 and complies with BfR (ISEGA Certificate) recommendations for direct contact with dry and moist, non-fatty food stuff.

Application Temperature                    : 0 °C / +50°C  
Product Functional Service Temperature: -40°C / +60°C

#### Liner

A super-calendered white glassine paper.

Basis weight    ISO 536                    : 60 gsm  
Caliper                    ISO 534                    : 54 µm

### PERFORMANCE CHARACTERISTICS

Properties	Test Method	Typical values
Initial Tack on Glass	FINAT FTM9	18.0 N/25mm
Adhesion to Stainless Steel	FINAT FTM2	9.0 N/25mm (20mins)
Total Product Caliper	ISO 534	134 µm

#### Shelf life

1 year when stored at 22°C and 50% RH