

**Product:** PH-220 QM Solvent Photo Paper

**Category:** Display & Visual - Latex, Solvent and UV Ink jet

**Country of Origin:** Australia

## Technical specifications:

Characteristics		Value
Substrate		205gsm Double Sides PE Coated Photo Based Paper
Coating	Coating type	25um Poly resin for Eco-sol
	Glossy	3-4 Gs /60° (High Matte)
	Whiteness	93-95
Opacity		94-95%(Matte)
Storage & Application	Shelf Time	4~5years
	Application Temperature	5~40 deg
	Durability	36 Months (Indoor)

Characteristics		Value
Substrate		205gsm Double Sides PE Coated Photo Based Paper
Coating	Coating type	25um25um PolyPoly resinresin forfor EcoEco - sol - sol
	Gloss	80 - 81 Gs /60° (High Gloss)
	Whiteness	93 - 95
Opacity		94 - 95%
Storage & Application	Shelf Time	4~5 years
	Application Temperature	5~40deg
	Durability	36 Months (Indoor)

# Technical specification sheet

**Ball & Doggett**  
ballanddoggett.com.au

## Conversion<sup>+</sup>

- |   |   |
|---|---|
| <input type="checkbox"/> Flat bed cutters     | <input type="checkbox"/> Cold overlaminating          |
| <input type="checkbox"/> Friction fed cutters | <input type="checkbox"/> Aqueous                      |
| <input type="checkbox"/> Die cutting          | <input checked="" type="checkbox"/> Latex inkjet      |
| <input type="checkbox"/> Thermal transfer     | <input checked="" type="checkbox"/> Eco Solvnt inkjet |
| <input type="checkbox"/> Screen printing      | <input checked="" type="checkbox"/> Solvent inkjet    |
| <input type="checkbox"/> Offset printing      | <input checked="" type="checkbox"/> UV curable Inkjet |

\*Always test with your combination of printer and inks prior to commercial use.

## Sheet Sizes

1370mm x 30m (Matt)	144565	1520mm x 30m (Matt)	144566
1370mm x 250m (Gloss)	147873	1520mm x 30m (Gloss)	147874

## Common applications

POP/POS Posters	
Display sign	
Arts/Photo graphics reproduction	