

**Product:** SharkSkin Wet Strength Board

**Category:** Display & Visual - Rigid Media

**Country of Origin:** Australia

## Technical specifications:

### Specification

Weight	900gsm
Caliper	1500um
Smoothness (TAPPI 555)	1.0 +0.5 PPS (um)
Brightness (TAPPI 525/ ISO 2470)	84 ±2 Top (%)
Gloss 75° (TAPPI 480)	>40 Hunter 75° (%)
Cobb (1min) (TAPPI 441)	≥ 45 Top (g/m <sup>2</sup> )
Cobb (2min) (TAPPI 441)	≥ 80 Back (g/m <sup>2</sup> )
Moisture (TAPPI 442)	6.5 - 9.5 (%)
Wet Strength adhesive	Tubibond L 1593 Aqueous acrylic copolymer with specialty auxiliaries

#### Note:

1. Test Climate 23 ± 1°C and 50±2% RH (TAPPI 402)
2. Tolerances based upon 95% confidence limits (for pallets and reels)
3. All specifications mentioned above may be subjected to technical changes

### Conversion<sup>+</sup>

- |   |   |
|---|---|
| <input type="checkbox"/> Flat bed cutters     | <input type="checkbox"/> Cold overlaminating          |
| <input type="checkbox"/> Friction fed cutters | <input type="checkbox"/> Aqueous                      |
| <input type="checkbox"/> Die cutting          | <input type="checkbox"/> Latex inkjet                 |
| <input type="checkbox"/> Thermal transfer     | <input type="checkbox"/> Eco Solvnt inkjet            |
| <input type="checkbox"/> Screen printing      | <input type="checkbox"/> Solvent inkjet               |
| <input type="checkbox"/> Offset printing      | <input checked="" type="checkbox"/> UV curable Inkjet |

\*Always test with your combination of printer and inks prior to commercial use.

### Sheet Size\*

1220mm x 2440mm

\* Made to order custom sizes

### Common applications

POS Solutions

Posters

Promotional display re Fridgerated areas