

Product: Wausau 100% Recycled Natural Kraft

Category: Roll Solutions: Roll Label



FACESTOCK DESCRIPTION: 55# 100% Recycled Natural Kraft Optimized for HP Indigo Presses

Recycled natural kraft has the coloring and consistency of a brown paper grocery bag. Recycled natural kraft gives a cozy, primitive, rustic, or "earthy" look for label applications. Perfect for candle labeling, art, crafts, gourmet foods, or on any label requiring a unique appearance. This paper is top coated and optimized for HP Indigo Presses.

| | |
|-----------------------------------|----------|
| Basis Weight (25 x 38 / 500), gsm | 81.4 |
| Caliper, microns | 147 |
| Tear, MD / CD, g | 79 / 101 |
| Tensile, MD / CD, kg | 13 / 4 |
| PCW, % | 100 |
| Recycled Content, % | 100 |

ADHESIVE DESCRIPTION: H-318

H-318 is the ideal choice for high end beverage and spirits, with improved resistance to moisture and humidity after bottling and at presentation to the consumer. H-318 is an aggressive, blended emulsion acrylic adhesive with the unique ability to combine special characteristics from different adhesives. H-318 was engineered to provide excellent high initial tack and quicker label adhesion onto glass while providing functional converting performance on an array of paper and film face stocks.

| | |
|-------------------------------|--------------------|
| Type | Hybrid |
| Classification | Emulsion Acrylic |
| Minimum Application Temp., °C | -26 |
| Service Temperature Range, °C | -29 to 79 |
| Regulatory Compliances | FDA 21 CFR 175.105 |

LINER DESCRIPTION: 40# SC

A supercalendered bleached liner. Superior die-cutting and stripping properties. Recommended for roll-to-roll applications. Good back printability.

| | |
|-----------------------------------|--|
| Basis Weight (25 x 38 / 500), gsm | 66 |
| Caliper, microns | 62.5 |
| Brightness, % | 78 |
| Gloss, 75°, % | 48 |
| Opacity, % | 65 |
| Tear, MD / CD, g | 32 / 34 |
| Tensile, MD / CD, kg | 15 / 9 |
| Regulatory Compliances | ASTM F963 Child Toy Safety, CONEG, RoHS, REACH |

All product specifications are for informational use only. Each customer and/or end user should determine the suitability of any product for their particular application. The above specifications are based on typical values and most current information. Specific products listed were current at the time of publication, however, all raw materials are subject to change.

Shelf Life: One year when stored at 72°F / 50% RH.